

varioPRINT 140 series

•
Built for business:
Class leading
production printer –
superb uptime and
outstanding image
quality

The Canon varioPRINT 140 series offers unparalleled reliability, impressive quality, green credentials and excellent output speeds, setting a new standard for monochrome production printing.



- Consistently high-quality prints thanks to Océ DirectPress technology
- Speeds of up to 143 images per minute
- Maximum output volume of 800,000 images per month
- Peerless reliability means the printer requires minimal maintenance
- Océ EnergyLogic delivers truly sustainable printing with zero ozone emissions
- HeatXchange technology further reduces energy consumption
- Embedded PRISMAsync controller offers intuitive operation and simplified scheduling
- Seamless workflow integration for smooth end-to-end production
- Range of inline accessories and DFD support for online finishing
- Superb registration, with excellent line-sharpness and halftone uniformity

TECHNOLOGY

Description

Black & white printer / scanner / copier

Imaging technology

Océ DirectPress®

Toner

Mono-component toner

Engine resolution

600 x 2400 dpi

Features

Toner Transfer Fusing (TTF) technology, HeatXchange technology, On-the-fly toner and paper refill; Automatic duplexing (up to 300 gsm), Active registration

Options

Operator attention light with adjustable warn-ahead functions, CCD interface

Print speed (simplex and duplex)

	A4	A3	SRA3
varioPRINT 140	143 ipm	75 ipm	70 ipm
varioPRINT 130	133 ipm	69 ipm	65 ipm
varioPRINT 115	117 ipm	61 ipm	58 ipm

varioPRINT 140

varioPRINT 130

varioPRINT 115

SEGMENT

Recommended monthly print volume (A4)

varioPRINT 140: 200,000-800,000
varioPRINT 130: 150,000-650,000
varioPRINT 115: 80,000-500,000

Maximum monthly print volume (A4)

varioPRINT 140: 2,200,000
varioPRINT 130: 2,000,000
varioPRINT 115: 1,700,000

GENERAL

User operation

Integrated 15" full colour touchscreen operator panel; Full engine / controller integration with one point of control PRISMAsync controller
Remote Control: iOS/Android application
Remote monitoring: on desktop via Remote User Interface
Remote Meter Reading: secure and easy transmission of meter readings
Remote Diagnostics: for maximum printer uptime
Remote Software Upgrade: always the latest software and functionality available

Warm-up time

150-270 seconds, depending on amount of toner in cleaner

First copy time

Simplex: 3.9 seconds

First print time

Simplex and ripped: 5.1 seconds

Registration tolerance

Maximum +/- 0.5 mm (A4 images)

Dimensions main engine (WxDxH)

1130 x 765 x 1040 mm (excluding user interface)
1130 x 765 x 1430 mm (including user interface)

Weight main engine

263 kg (with Scanner / Automatic document feeder)

Certificates

EPA Energy Star®/ TEC compliance, RoHS, Cetecom / CE Class A, FCC Class A, UL / TÜV / CE, REACH

Product Safety & Environment

EPA/TEC compliance, RoHS compliance, Cetecom / CE Class A, FCC Class A, UL / TÜV / CE, VCCI, ERP, China RoHS, CRDH FDA (USA), WEEE, Green Procurement Standards, EAC, KC, RCM, International Energy Star

Other compliances

Section 508, EPEAT BRONZE, De-inkability certificate

Operating system

Windows 10

Processor

2.7 GHz

Memory

4 GB

Hard disk

500 GB

Interface

10/100/1000 Base-T

Page Description Language

APPE (Adobe® PDF Print Engine): Adobe® PostScript® 3™/streaming PostScript®; PPL/PA Level 1; PPL versions 1.5, 2.1 and 2.2
PDF 1.7; PCL 6; XPS; IPDS (options); Xerox® PPP support

Fonts

136 Type1 fonts for roman languages
Use of PostScript fonts via Settings Editor

Protocols

TCP/IP (LPR/LPD, socket), SMB static/auto IP (via DHCP), SNMP v1-v3 (printer MIB, private MIB), Job monitoring MIB, IPP

Printer drivers

PS3 UPD - Windows Server 2003(R2) / Vista / Windows Server 2008 / Windows 7 / Windows Server 2008 R2 / Windows 8 / Windows server 2012 / Windows 8.1 / Windows 2012 R2 / Windows 10
PS3 PPD - legacy Windows and MAC/Linux-CUPS/other
PS3 - Macintosh (Mac OS 10.6/10.7/10.8/10.9/10.10/10.11/10.12)
PCL6 UPD - Windows Server 2003(R2)/Vista/Windows Server 2008 / Windows 7 / Windows Server 2008 R2 / Windows 8 / Windows server 2012 / Windows 8.1 / Windows 2012 R2 / Windows 10
PCL6 GPD - legacy Windows and MAC/Linux-CUPS/other
Microsoft XPS UPD - Microsoft Windows Client Vista / Windows Server 2008 / Windows 7 / Windows Server 2008 R2 / Windows 8 / Windows server 2012 / Windows 8.1 / Windows 2012 R2 / Windows 10
SAP Device Type (SAP R/3 4.6 and higher)

Security

Common Criteria EAL 2+, E-shredding, HTTPs, Firewall, PIN for Doc Box, User authentication to SDS, Removable hard disk, IPv6, software protection license (integrity checker), user authentication per user role: key operator, system administrator and service representative

Features

Schedule (8 hours ahead), DocBox for advanced job editing, One queue and job management for copying and printing, Spool-while-rip-while-print-while-clean-up, Multi-job processing, Multitasking (print / copy / scan), JDF connector compatible, Remote Meter Reading, Remote Diagnostics, Remote Software Upgrade and remote control

Optional licenses

DocBox, Schedule, Remote Viewer, Scan to file/e-mail, E-shredding, Multiple queues, Streaming printing, Accounting, Remote Service, Font sets: Korean, Japanese, Simplified Chinese, Traditional Chinese, DPLink (integration in customer Xerox infrastructure), KDKLink (integration in customer Kodak infrastructure)

ENVIRONMENTAL

Sound power level

Ready mode: max 33dB
Print mode: max 64dB

Ozone emissions

None (engine)

Power requirement

1-Phase, 200 - 240 V; 50/60 Hz

Power consumption

Ready mode: 270W
Low power mode: 150W
Sleep mode: 4.5W (excl. controller)
Operation (duplex): vP115: 1.9kW
vP130: 2.0 kW
vP140: 2.2 kW

Optimum temperature & Relative humidity

17° C - 30° C / 20% - 80%

Room ventilation

50 m³ or >2AC/hr at room size > 50 m³

INTERNAL PAPER MODULE

Paper trays

2 x 1500 sheets (80 gsm)
2 x 500 sheets (80 gsm)

Paper size and weight

50 - 300 gsm
A4, B5 and A5 (bulk trays 1+2)
140 x 182 mm - up to 320 x 432 mm (tray 3)
140 x 182 mm - up to 320 x 488 mm (tray 4)

Paper feed technology

Friction feed, Paper Logic from all trays

EXTERNAL PAPER MODULE-D1

Description

Optional external paper input module with single or dual paper trays

First module

2 x 1700 sheets (80 gsm, all sizes)
2 x 600 sheets (80 gsm, all sizes)
Dual configuration: max. 2 x 3400 sheets (80 gsm, A4)
2 x 600 sheets (80 gsm, all sizes)

Maximum paper capacity

8,000 sheets (A4 80 gsm) / 4,600 sheets (all sizes)

Paper size and weight

50 - 300 gsm
203 x 203 mm - 320 x 488 mm (all trays)

Paper feed technology

Suction feed, Air separation, Paper Logic from all trays

Dimensions (WxDxH)

987 x 743 x 1056 mm

Weight unit

203 kg

Power requirement

90-264 V, 40-67 Hz, 200 W

Features

Automatic paper size detection, Tray-empty detection, On-the-fly paper loading, Paper-level indication, Tab sheet processing, Custom paper size support, Optional dual paper trays

PRINTING

Job management

DocBox, Queue and History, Waiting Room

Print resolution

Adobe PostScript 3: 1200 x 1200 dpi, 600 x 2400 dpi
PCL: 600 x 600 dpi

Maximum printable area

Adobe PostScript 3: 3 mm from side, maximum 308 x 484 mm
PCL: 6 mm

Screen frequency

PCL: maximum 106 lpi
Adobe PostScript 3: maximum 200 lpi

Grey levels

Adobe PostScript 3: 200
PCL: 125

Features

RIP at rated engine speed, Pre-RIP, Print-while-rip-while-spool (Streaming), Mixplex, Hotfolder & multiple queue support

COPYING

Copy resolution	600 x 1200 dpi
Exposure control	Auto / Manual (9-step scale), Text, Text / Photo, Photo
Zoom	25 - 400%; automatic
Screen frequency	200 lpi
Grey levels	200
Features	Automatic quality optimization for text / photo

SCANNING

Resolution	75, 100, 150, 200, 300 (default), 600 dpi
Colour scanning	Optional
Destination	Scan-to-Email, Scan-to-DocBox, Scan-to-FTP, Scan-to-USB
File format	PDF (single-page and multiple-page), TIFF, JPEG / sRGB (colour scanning)
Features	Thumbnail preview (DocBox), Scan profiles, Status overview, Scan-once-print-many, Scan-while-warming up, Scan-while-print, Subset-scanning, RGB color scanning, Scan to File mixed sizes

DUPLEX COLOUR IMAGE READER-L1

Capacity	300 sheets (80 gsm)
Maximum resolution	600 x 600 dpi
Maximum scan speed	A4, Black& white/colour, 300 x 300 dpi: 120 ipm A4, Black & white, 600 x 600 dpi: 100 ipm A4, Colour, 600 x 300 dpi: 105 ipm A4, Colour, 600 x 600 dpi: 25 ipm
Auto detectable original size	A3, A4, A4R, A5, A5R, Free sizes (W x L): Min. 139.7 mm x 128 mm, Max. 432 mm x 304.8 mm
Paper weight	1-sided: 38 - 220 gsm 2-sided: 50 - 220 gsm

DOCUMENT INSERTION UNIT-N1

Number of Trays	2-bin
Tray Capacity	200 sheet / bin
Paper Weight	52 - 300 gsm
Paper Size	A3, A4, A4R, SRA3, 13"x19", Free size (182 x 182 mm to 330.2 x 487.7 mm)
Power Source / Consumption	230V 10A
Dimensions	336 mm (746 mm including Tray) x 793 mm x 1407 mm
Weight	Approx 61 kg

HIGH CAPACITY STACKER-H1

Stack Tray Capacity	Stack tray: 6,000 sheets (80 gsm) in two stacks of 3,000 sheets each
Top Tray Capacity	Top Tray: 200 sheets
Acceptable Paper Weight	50 - 300 gsm
Acceptable Paper Size	Max defined for main engine. Custom sizes between min. 140 x 182mm up to 320 x 488mm, mixed sizes, tabs and folded sheets 230V 10A (2nd Stacker can get power from 1st Stacker)
Optionals	DFD interface kits for 860 mm and 1002 mm
Dimension	899 x 745 x 1040 mm
Weight	Approx 210 kg

PAPER FOLDING UNIT-J1

Basic Information	Z Fold, C Fold, Zigzag Fold, Double Parallel
Acceptable Paper Weight	50 - 105 gsm Double parallel: 50 - 90 gsm
Acceptable Paper Size	A4R Z-fold: A3, B4
Power Source	From Finisher-W1 or Saddle Finisher-W1
Dimension	336 x 793 x 1190 mm
Weight	Approx 71 kg

FINISHER-W1

Basic Information	Staple and stacking finisher
Number of Trays	2
Upper Tray (A) Capacity	A4/A4R/A5R 1,000 sheets, A3 1,000 sheets, SRA3/13"x19" 1,000 sheets
Lower Tray (B) Capacity	A4 4,000 sheets, A4R 2,000 sheets, A3 1,500 sheets, SRA3 1,000 sheets
Stapled stacking capacity	A4 200 sets or max 3,000 sheet
Stapling Position	Corner, Double
Acceptable Paper Weight	50 - 300 gsm
Staple Capacity:	A4: 100 sheets, A3/A4R: 50 sheets
Power Source	230V x 10A
Dimension	800 x 792 x 1239 mm
Weight	130 kg

BOOKLET FINISHER-W1

Basic Information	Same functionality as Finisher W1 and additional saddle stitching and V-folding functionality Up to 100 pages booklet available (2 - 25 sheets) Stack capacity up to 5000 sheets and up to 100 sheets stapled
Number of Trays	2
Upper Tray (A) Capacity	1,000 sheets A4/A4R/A5R, 1,000 sheets A3, 1,000 sheets SRA3/13"x19"
Lower Tray (B) Capacity	A4 4,000 sheets, A4R 2,000 sheets, A3 1,500 sheets, SRA3 1,000 sheets
Stapled stacking capacity	A4 200 sets or max 3,000 sheet
Stapling Position	Corner, Double
Acceptable Paper Weight	50 - 300 gsm
Booklet stitch paper size	A3, A4R, SRA3, 13"x19", Free size 210 x 279.4 mm to 330.2 x 487.7 mm
V-Folding	Up to 5 sheets
Power Source	230V x 10A
Dimension	800 x 792 x 1239 mm
Weight	Approx 180 kg

BOOKLET TRIMMER-F1

One Edge Trimming	Fore-edge
Trim Width	2 - 28 mm
Trim Thickness	Up to 50 sheets (includes Cover, by half fold)
Acceptable Paper Weight	50 - 300 gsm
Output Tray Capacity	30 booklets
Power Source	Booklet finisher W1
Dimension	2,095 mm (including joint, conveyer and output tray: 162 mm) x 790 mm x 1,040 mm
Weight	Approx 152 kg

TWO-KNIFE BOOKLET TRIMMER-A1

Basic Information	Top and Bottom Edge trim
Trim Width	2 - 15 mm
Trim Thickness	Up to 50 sheets (includes Cover, by half fold)
Acceptable Paper Weight	50 - 300 gsm
Output Tray Capacity	30 booklets
Power Source	230V x 10A
Dimension	536 x 770 x 1040 mm
Weight	Approx 145 kg

Punch Unit BT1 / BU1

Basic information

Punch Hole type

Acceptable Punch Paper Weight:

Acceptable Punch Paper Size:

Weight:

Requires either the Booklet Finisher W1 or Staple Finisher W1
BT1: 2 holes and 4 holes (FRN) selectable, BU1: 4 holes (Swe)
52 - 300 gsm

2 holes: A3, A4, A4R, Free size (182 x 182 to 297 x 432.0 mm)
4 holes: A3, A4, Free size
(257 x 182 mm to 297 x 432 mm)
Approx 7.7 kg

MULTIFUNCTIONAL PRO PUNCHER-B1

Basic information

Acceptable Paper Weight:

Acceptable Paper Size

Punch tools

Power source

Dimensions

Weight

External In-line Punch Unit

75 - 300 gsm (Plain paper), 118 - 300 gsm (Coated paper),
157 - 300 gsm (Crease/ Plain & Coated paper)

Punch: A4, A4R, SRA4, A3, SRA3

Crease: A4R, A3, SRA3, 13 x 19

Plastic Comb 21-Hole, Twin Loop 23-Hole (Round/Rectangle),
Twin Loop 34-Hole (Round/Square), Color Coil 47-Hole,
Velo Bind 12-Hole, Loose Leaf 4-Hole Punch, Loose Leaf 2-Hole
Punch, Loose Leaf 4-Hole (Swedish), Loose Leaf 3-Hole, Crease
230V x 2A

445 mm x 795 mm x 1040 mm

Approx 102 kg

OUTPUT TRAY

Basic information

Paper Size:

Paper Weight

Output Capacity

Dimensions

Weight

Basic tray face-up / face-down stacking

All available size on marking engine

50 to 300 gsm

250 sheets at simplex printing/100 sheets at duplex printing

360 mm x 547 mm x 256 mm

Approx. 4.2 kg

3RD PARTY FINISHER

Basic information

The varioPRINT 140 series can be configured also with
3rd party finishing. Please find here a list of listed and
approved finishers
Plockmatic Pro 50 and Pro 35 Booklet makers
BLM300 Booklet maker
BLM600 Booklet maker
Max Ringbinder